


MMBTSC2712

NPN Silicon Epitaxial Planar Transistor

for audio frequency general purpose amplifier applications.

The transistor is subdivided into four groups O, Y, G and L, according to its DC current gain.




1.BASE 2.EMITTER 3.COLLECTOR
TO-236 Plastic Package

Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)

Parameter	Symbol	Value	Unit
Collector Base Voltage	V_{CBO}	60	V
Collector Emitter Voltage	V_{CEO}	50	V
Emitter Base Voltage	V_{EBO}	5	V
Collector Current	I_C	150	mA
Base Current	I_B	30	mA
Power Dissipation	P_{tot}	200	mW
Junction Temperature	T_J	125	$^\circ\text{C}$
Storage Temperature Range	T_{stg}	- 55 to + 125	$^\circ\text{C}$

Characteristics at $T_{amb}=25^\circ\text{C}$

Parameter	Symbol	Min.	Max.	Unit
DC Current Gain at $V_{CE} = 6 \text{ V}$, $I_C = 2 \text{ mA}$	h_{FE}	70	140	-
Current Gain Group O Y G L	h_{FE}	120	240	-
	h_{FE}	200	400	-
	h_{FE}	350	700	-
	h_{FE}			
Collector Base Cutoff Current at $V_{CB} = 60 \text{ V}$	I_{CBO}	-	100	nA
Emitter Base Cutoff Current at $V_{EB} = 5 \text{ V}$	I_{EBO}	-	100	nA
Collector Emitter Saturation Voltage at $I_C = 100 \text{ mA}$, $I_B = 10 \text{ mA}$	$V_{CE(sat)}$	-	0.25	V
Transition Frequency at $V_{CE} = 10 \text{ V}$, $I_C = 1 \text{ mA}$	f_T	80	-	MHz
Collector Output Capacitance at $V_{CB} = 10 \text{ V}$, $f = 1 \text{ MHz}$	C_{ob}	-	3.5	pF








SEMTECH ELECTRONICS LTD.



Dated: 16/03/2015 Rev: 01

MMBTSC2712



SEMTECH ELECTRONICS LTD.



Dated: 16/03/2015 Rev: 01